

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number  
**WO 2004/112286 A1**

(51) International Patent Classification<sup>7</sup>: **H04B 10/152**,  
H04J 14/02

(21) International Application Number:  
PCT/JP2004/008577

(22) International Filing Date: 11 June 2004 (11.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003-169067 13 June 2003 (13.06.2003) JP

(71) Applicant (for all designated States except US): MAT-  
SUSHITA ELECTRIC INDUSTRIAL CO., LTD.  
[JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka  
5718501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): YASUE, Toshihiko.  
FUSE, Masaru.

(74) Agent: OGASAWARA, Shiro; Daisan-Longev' Bldg.,  
3-11, Enokicho, Suita-shi, Osaka 5640053 (JP).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SI, SK,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: OPTICAL TRANSMISSION SYSTEM; AND TRANSMITTER, RECEIVER AND SIGNAL LEVEL ADJUSTMENT  
METHOD FOR USE THEREIN



(57) Abstract—In a transmitter (11), a peak detection section (104) detects a peak factor of a frequency division multiplexed signal which is output from a frequency division multiplex section (103). A spurious calculation section (105) instructs a gain adjustment section (106) to adjust the signal level of the frequency division multiplexed signal so that the level of spurious components (e.g., adjacent channel leakage power ratio (ACLR)) is equal to or less than a predetermined level, based on the peak factor.